



FH26P | Duration II 32

DESIGN

| | |
|--------------------|-------------------------------------|
| Product Type | PDI (Precision Dye Injection) |
| Construction | Tufted |
| Surface Texture | Level Patterned Cut |
| Gauge | 1/10" |
| Stitches Per Inch | 14.5 |
| Dye Method | Precision Dye Injection |
| Backing Material | Weldlok® |
| Fiber Type | Colorstrand® Nylon with ColorShield |
| Tufted Face Weight | 32.00 oz per sq yd |
| Pile Thickness | .207" |
| Density | 5,565 |
| Weight Density | 178,080 |
| Width | 12', 13'6", 15' |

SUSTAINABILITY

| | |
|-------------------------------|----------|
| Iaq Green Label Plus | 6678 |
| Pre Consumer Recycled Content | 51% |
| Nsf 140 | Gold |
| Declare Label | Declared |

PERFORMANCE

| | |
|---------------|--------------------------------------|
| Static | Less than 3.5 K.V. |
| Flammability | Meets or exceeds requirement Class 1 |
| Smoke Density | 450 or Less |

SERVICE

| | |
|------------|--|
| Warranties | 10 Year Limited Wear Warranty, Lifetime Static |
|------------|--|

DURKAN

contact us: 800.241.4580 tech services: 800.833.6954 durkan.com a division of **Mohawk Group**